


Bitrix is a totally recessed indoor luminaire, made of AirCoral®, that is adjustable up to $\pm 30^\circ$. It is available in 3000K standard and is suitable for installation in plaster ceilings.



TECHNICAL DATA


Wattage / Input	9W per beam (500mA)
Power Supply	Remote, not included. See page 2.
Construction	Body: AirCoral®
CCT	3000K 2700K, 4000K on request
CRI	>90
Initial Lumens	1125 lm per beam (3000K)
Efficacy	Coming Soon
Optics	40°
Finishes	AirCoral® Plaster
Fixture Dimensions	10.83" l x 5.91" w x 5.12" h
Cutout Dimensions	11.22" x 6.30"
Aperature	8.27" x 3.54"
Fixture Weight	4.41 lbs
IP Rating	IP20

The body is made of AirCoral® a unique patented composite material that actually purifies the air. It can be calculated how many cubic feet each fixture will purify. See website for AirCoral® calculator.

Additionally, AirCoral® is:

- Antibacterial.
- Antifungal.
- Scratch-resistant.
- Dust-resistant.
- Suitable for painting.
- LEED recognized material.

Fixture Dimensions



ORDERING INFORMATION

Example: BU6343.Z.AC.30.US. Power supplies ordered separately.

BU6343.Z	AC		.US
Model No.	Material	CCT	
BU6343.Z	AC - AirCoral®	30 - 3000K (standard) 27 - 2700K (on request) 40 - 4000K (on request)	.US

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

500mA

Part Number	Description	Input/Output	Fixtures
PPLT00527	Phase Dim (120V only)	120VAC to 500mA, 25W, Class 2, IP66	1-1
PPLT00467-P	0-10V Dimming to 1.0%	120-277VAC to 500mA, 50W, Class 2, DAMP	1-1
PPLT00561-P	0-10V Dimming to 0.1%	120-277VAC to 500mA, 100W, Class 2, DAMP	1-1

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00180	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 500mA, 27W, Class 2	1-1

For other power supply options consult factory.

PHOTOMETRIC DATA

*Coming Soon**Job Name/Date:**Fixture Type Designation:*