


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 3.5 is the 2.8" x 2.8" square, static white version. (Not suitable for use in immersion in swimming pools or fountains).



TECHNICAL DATA

Wattage / Input	2W (24VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: Polyurethane Resin Cable Length: 4.92' standard (16.4" available)
CCT	2200K, 2700K, 3000K, 4000K
CRI	>80
BUG Rating	B0-U3-G0 (3000K)
Delivered Lumens	54 lm (3000K)
Efficacy	27 lm/W
Optics	Diffuse
Fixture Dimensions	2.76" x 1.42" h
Fixture Weight	0.57 lbs
LED Source	1 Mid-power LED
Lumen Maintenance	L80, B10 >60,000 hrs (Ta 25°C)
Color Consistency	3-Step MacAdam
Operating Temp.	-20°C to +45°C
IP Rating	IP65, IP68 IP69 (Water Temp Not Exceed 35° C)
IK Rating	IK10
Walkover	Yes

Fixture Dimensions



ORDERING INFORMATION

Example: GA35000000N0DR or GA35000000N0DR-1. Accessories / Power Supplies ordered separately.

GA3500	0000		0D	R	
Model No.		CCT	Optics	Finish	Cable Length
GA3500	0000	N - 2200K F - 2700K 5 - 3000K 9 - 4000K	0D - Diffused	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC

Part Number	Description	Input/Output	# of Fixtures
PPLT00284	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, DAMP	1-40
PPLT00543	0-10V Dimming to 15% (-40°C / -40°F cold weather start)	120-277VAC to 24VDC, 100W, Class 2	5-40

Suggested Lutron Compatible

Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00530	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-38

DRIVERS IN NEMA ENCLOSURE

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-38


For other power supply options consult factory.

Job Name/Date:

Fixture Type Designation:


ACCESSORIES

Installation



WCA10

Outer Casing
For in-grade use



WCA28

Outer Casing
For Plasterboard



WL0100


Suction Cup

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 18.6

— C0 - C180
— C90 - C270



PHOTOMETRIC FILENAME : NEW_GOCCIA_3.5_D_3000K_2W_24VDC.IES

Job Name/Date:

Fixture Type Designation: