


Goccia is a family of outdoor step lights that are ideal for accent and pathway guidance lighting. They are available in round or square versions, 3 sizes, static white or RGB, and that can be installed flush with the surface using an outer casing, or wall mounted. Goccia 3.8 is the Ø2.8" round, RGB version. (Not suitable for use in immersion in swimming pools or fountains).



Fixture Dimensions



TECHNICAL DATA

Wattage / Input	3.5W (24VDC)
Power Supply	Remote, not included. See page 2.
Construction	Body: Polyurethane Resin Cable Length: 4.92' standard (16.4" available)
CCT	RGB
BUG Rating	B0-U3-G0
Delivered Lumens	50 lm: (R) 15 lm, (G) 34 lm, (B) 7 lm
Efficacy	14.3 lm/W: (R) 4.29 lm/W, (G) 9.71 lm/W, (B) 2 lm/W
Optics	Diffuse
Fixture Dimensions	Ø2.76" x 1.42" h
Fixture Weight	0.47 lbs
LED Source	12 Mid-power, Full-color LEDs
Lumen Maintenance	L80, B10 >50,000 hrs (Ta 25°C)
Color Consistency	—
Operating Temp.	-20°C to +45°C
IP Rating	IP65, IP68 IP69 (Water Temp Not Exceed 35° C)
IK Rating	IK10
Walkover	Yes

ORDERING INFORMATION

Example: GA3800P0060DR or GA3800P0060DR-1. Accessories / Power Supplies ordered separately.

GA3800	0P00	6	0D	R	
Model No.		CCT	Optics	Finish	Cable Length
GA3800	0P00	6 - RGB	0D - Diffused	R - Resin	4.92' standard 1 - 16.40'

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC - *For use as in-grade uplights*


Part Number	Description	Input/Output	# of Fixtures
PPLT00288-P	DMX / RDM (Field Addressable) / DALI (4 Channels)	120-277VAC to 24VDC, 100W, Class 2	1-20

For other power supply options consult factory.

ACCESSORIES - Installation



WCA07
Outer Casing
For in-grade use



WCA27
Outer Casing
For Plasterboard




WL0100
Suction Cup

PHOTOMETRIC DATA

Note: All photometry is 3000K

Maximum Candela = 17.5



PHOTOMETRIC FILENAME : NEW_GOCCIA_3.8_D_RGB_3.5W_24VDC.IES

Job Name/Date:

Fixture Type Designation: