

EASY LINE - Transparent LL10


EASY LINE is a vertical, bendable LED strip that is IP65-IP68 rated ideal for fountains or swimming pools for panel installation in reinforced concrete with tiles or pool liner. It is available in Transparent, Frost, Clear or Total Light with static white, tunable white or RGB, and guarantees protection against UV rays and the corrosive action of salt and sodium hypochlorite. EASY LINE Transparent has a transparent outercasing. **Not cuttable in the field.**



TECHNICAL DATA

Wattage	11W / 3.28 ft (1 m)	
Power Supply	Remote Fountain/Pool Approved 24VDC Power Supply, not included. See page 2.	
Construction	Body: Transparent Resin Outercase: Transparent UV-treated PVC	
CCT	3500K, 3900K, 6000K (204 LED / 3.28') Warm White on request: 2200K, 2600K, 2900K	
CRI	85	
Delivered Lumens	1110 lm / 3.28' (3500K) 1065 lm / 3.28' (3900K)	1050 lm / 3.28' (6000K)
Efficacy	100.9 lm/W (3500K) 98.8 lm/W (3900K)	95.5 lm/W (6000K)
Optics	120°	
Fixture Dimensions	0.37" w x 0.26" h x Various Lengths	
Bend Radius	2.36"	
LED Source	SMD 3014	
LED Spacing	204 LED per 3.28 ft (1 m), 0.20" between LEDs	
Lumen Maintenance	L80,B10>50,000 hrs	
Color Consistency	2-3-Step MacAdam	
Operating Temp.	-22°F to 131°F	
IP Rating	IP65 / IP68	

Fixture Dimensions



NOT CUTTABLE IN THE FIELD

**MUST USE SUITABLE APPROVED
FOUNTAIN & SWIMMING POOL
POWER SUPPLY WHICH
IS REMOTELY MOUNTED**

ORDERING INFORMATION

Example: LL10E-N.24.68.T.X.US Power Supplies / Accessories ordered separately.

LL10E	-		.	24	.		.	T	.		.	US
Model No.	CCT		Power		IP Rating				Cable Exit			
LL10E - 204 LED / 3.28' (1 m)	V - 3500K	Warm White	24 - 24VDC		65 - IP65		T - Transparent		X - End Feed		US	
NOTE: Available in lengths up to 75 feet. Please specify length when ordering.	W - 3900K	On Request			68 - IP68				Z - Back Feed			
	N - 6000K	V8 - 2200K							NOTE: Back Feed (Z) only available on IP65 versions			
		V2 - 2600K										
		V5 - 2900K										

NOTE: Available in lengths up to 75 feet. Please specify length when ordering.

Job Name/Date:

Fixture Type Designation:

SUGGESTED POWER SUPPLIES

24VDC - **TO BE USED WITH FOUNTAIN / SWIMMING POOLS**

Part Number	Description	Input/Output	# of Fixtures
FPV-100110024	ELV / TRIAC & 0-10V Dimming (100 to 0%)	120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X	1-6
FPV-100000024	Non-Dim	120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X	1-7
FPV-100100024	0-10V Dimming (2 Channels)	120-277VAC to 24VDC, 100W, Class 2, IP66, NEMA 4X	1-14

DRIVERS IN NEMA 4X ENCLOSURE - **FOR INDOOR/OUTDOOR USE ONLY**

Remote 24VDC - ELV / TRIAC / 0-10V



PPLT00715

Part Number	Description	Input/Output	# of Fixtures
PPLT00715	ELV / TRIAC / 0-10V Dimming to 0.1%	120-277VAC to 24VDC, 96W, Class 2, WET/DAMP	1-6

Suggested Lutron Compatible - **FOR INDOOR/OUTDOOR USE ONLY**


Part Number	Option	Lutron SKU	Dim Range	Description	Input/Output	# of Fixtures
PPLT00273	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 40W, Class 2	1-2
PPLT00530	L3DAE / L3DA3W	L3DA	100%-1%	Hi-Lume™ 1% EcoSystem™ or 1% 3-Wire LED Driver	120-277VAC to 24VDC, 96W, Class 2	1-6

For other power supply options consult factory.

PHOTOMETRIC DATA

3500K


Maximum Candela = 266.3



PHOTOMETRIC FILENAME : EASY LINE TRANSPARENT LL10.SVF24-6568.T 3500K.IES

3900K


Maximum Candela = 286.2



PHOTOMETRIC FILENAME : EASY LINE TRANSPARENT LL10.SWF24(R).T 3900K.IES

6000K

Maximum Candela = 251.4




PHOTOMETRIC FILENAME : EASY LINE TRANSPARENT LL10.SNF24-6568.T 6000K.IES

Job Name/Date:

Fixture Type Designation:


ACCESSORIES

Installation / Mounting for 0.37x0.26 inch



Code	Finishing	Description
PRO-AL-9.5x6.5-AL	Aluminum	Rigid guide L max 9.84 ft
OUT-S-9.5x6.5.W OUT-S-9.5x6.5.F	White Opal	Silicone profile
CLIP-S-9.5x6.5.W CLIP-S-9.5x6.5.F	White Opal	Silicone clip
CLIP-AC-9.5x6.5-AC	AISI 304 harmonic steel	Steel clip
PRO-AC-9.5x6.5-AC	AISI 316 harmonic steel	Rigid guide L max 8.20 ft

POWER CABLE EXIT / AREA WITH REDUCED LIGHT



Job Name/Date:

Fixture Type Designation: